

4AW

5-6 WATT WIDE INPUT DC-DC CONVERTERS

Features:

- 5-6W Isolated Output
- Efficiency to 82%
- Regulated Outputs
- Continuous Short Circuit Protection
- 24-Pin DIP Package
- 4 : 1 Input Range
- Pi Input Filter

MODEL NUMBER	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT	INPUT CURRENT		% EFF.	CASE
				NO LOAD	FULL LOAD		
4AW01		5 VDC	1000 mA	15 mA	267 mA	78	
4AW02		12 VDC	470 mA	15 mA	287 mA	82	
4AW03		15 VDC	400 mA	15 mA	305 mA	82	
4AW04	9-36 VDC	±12 VDC	±230 mA	25 mA	281 mA	82	A
4AW05		±15 VDC	±190 mA	25 mA	290 mA	82	
4AW06		±5 VDC	±500 mA	25 mA	267 mA	78	
4AW11		5 VDC	1000 mA	7.5 mA	130 mA	80	
4AW12		12 VDC	470 mA	7.5 mA	143 mA	82	
4AW13		15 VDC	400 mA	7.5 mA	153 mA	82	A
4AW14	18-72 VDC	±12 VDC	±230 mA	12 mA	141 mA	82	
4AW15		±15 VDC	±190 mA	12 mA	145 mA	82	
4AW16		± 5 VDC	±500 mA	12 mA	134 mA	78	

NOTE: 1. Nominal Input Voltage 24 or 48 VDC



D1 International, Inc.

95 E. Main St. Huntington, Ny 11743 USA • 631-673-6866 • Fax: 631-673-6893
www.d1international.com • e-mail: d1intl@aol.com



INPUT SPECIFICATIONS:

Input Voltage Range.....	24V.....	9-36V
	48V.....	18-72V
Input Filter.....		Pi Type

OUTPUT SPECIFICATIONS:

Voltage Accuracy.....		± 1.0% max.
Voltage Balance (Dual).....		± 1.0% max.
Temperature Coefficient.....		± 0.05% / °C
Ripple and Noise, 20MHz BW, Single.....		75mV p-p max.
	Dual.....	1% p-p max.
Short Circuit Protection.....		Continuous
Line Regulation ¹ , Single/Dual.....		± 0.5% max.
Load Regulation, Single ²		± 0.5% max.
	Dual ³	± 1.0% max.

GENERAL SPECIFICATIONS:

Efficiency.....		See Table
Isolation Voltage.....		3KVDC min
Isolation Resistance.....		10 ⁹ ohms
Switching Frequency.....		200KHz, min
Operating Temperature Range.....		-25°C to + 71°C
Case Temperature (Plastic case).....		95°C max.
	(Copper case).....	100°C max.
Cooling.....		Free-Air Convection
Storage Temperature Range.....		-40°C to + 100°C
Dimensions.....		1.25 x 0.8 x 0.4 inches (31.8 x 20.3 x 10.2mm)

ISOLATION VOLTAGE:

1.5 KVDC min.....Suffix "M" Models

CASE MATERIAL:


Standard Models.....	Non-Conductive Black Plastic
Suffix "M" Models.....	Black Coated Copper with Non-Conductive Base

NOTE:

1. Measured From High Line to Low Line
2. Measured From Full Load to 10% Load
3. Measured From Full Load to 1/4 Load

CASE A

NOTE: Pin Size is 0.02" inch (0.5mm) DIA or .020 x .014 Inch
All Dimension In Inches(mm)



PIN CONNECTION 1.5K VDC & 3K VDC		
Pin	Single Output	Dual Output

1	NP	NP
2	-V Input	-V Input
3	-V Input	-V Input
5	NP	NP
9	NC	Common
10	NC	NC
11	NC	-V Output
12	NP	NP
13	NP	NP
14	+V Output	+V Output
15	NC	NC
16	-V Output	Common
22	+V Input	+V Input
23	+V Input	+V Input
24	NP	NP

*NP-NO PIN

*NC-NO CONNECTION WITH PIN

All Specifications Typical At Nominal Line, Full Load and 25°C Unless Otherwise Noted.